

GRAPHIC PRESS WASH

DYNACHEM Graphic Press Wash is designed to remove all inks from screen printing mesh. This product evaporates quickly and can be used during on-press color changes, before storing screens, or for removing ink from squeegees, floodbars and other equipment.

FEATURES

- Effectively dissolves most inks, including conventional/solvent, UV, plastisol, water based, silver, and carbon.
- Non-flammable, making it safer for handling, storage, and rag disposal than conventional solvent cleaners.
- Dries fast, providing a safe odor-free alternative to hazardous flammable solvents.
- Can be applied manually or in an enclosed automatic screen washing system, providing superior product life and economy.

INSTRUCTIONS

- Scrape any excess ink from screen.
- Apply DYNACHEM Graphic Press Wash by squirt bottle, pneumatic sprayer, or rag to the ink side of the screen.
- Thoroughly agitate ink with a rag or scrubber, then wipe up all dissolved ink.
- Reapply if necessary, and follow with a dry rag, wiping on both sides of the screen.
- The screen will be ready for printing or tape application within 20 seconds.
- **NOTE:** DYNACHEM Graphic Press Wash should not be rinsed with water.

PROPERTIES

APPEARANCE / ODOR

**Clear liquid,
aromatic odor**

SPECIFIC GRAVITY

0.92-0.93 @ 68°F (20°C)

pH

Neutral

VOC

930 grams/liter

FLASH POINT

142°F (61°C)

INK TYPES

**Plastisol, UV,
Conventional/Solvent,
Water Based**

PRODUCT FAMILY

Textile, Graphic