

TEXTILE PRESS WASH

DYNACHEM Textile Press Wash is designed to remove plastisol ink from screen printing mesh. It evaporates quickly and can be used during on press color changes, before storing screens, or for removing ink from squeegees, floodbars and other equipment.

FEATURES

- Has a citrus odor, making the job of color changes and screen reclaiming much more pleasant.
- Dries safe, providing a safe, odor-free alternative to mineral spirits, aerosol screen opener and other hot, hazardous, and flammable solvents.
- Non-flammable, making it safer for handling, storage, and rag disposal than conventional solvents.
- Can be applied manually or in an enclosed automatic screen washing system, providing superior product life and economy.

INSTRUCTIONS

- Scrape any excess ink from screen.
- Apply DYNACHEM Textile Press Wash by squirt bottle, pneumatic sprayer or rag to the (well) ink side of the screen.
- Thoroughly agitate ink with a rag or a scrubber, then wipe up all dissolved ink.
- Reapply if necessary, and follow with a dry rag, wiping on both sides of the screen.
- The screen will be ready for printing or tape application within 10-15 seconds.

PROPERTIES

APPEARANCE / ODOR

**Clear liquid,
citrus odor**

SPECIFIC GRAVITY

0.80 @ 68°F (20°C)

pH

Neutral

VOC

800 grams/liter

FLASH POINT

142°F (61°C)

INK TYPES

Plastisol

APPLICATION

Textile