

DYNASILVER™

DYNAMESH DynaSilver™ is a 1 mil (0.025 mm) silver metalized polyester screen tape coated with a permanent acrylic adhesive.

ADVANTAGES

- Strong adhesion to a wide range of substrates
- Excellent solvent resistance
- So thin it can be used very close to the screen image

APPLICATIONS

- Protect frame adhesive from aggressive inks and solvents
- Protect screen mesh from sharp substrate edges

USAGE

- Remove tape from backing liner and apply to clean, dry surface free of debris.

PACKAGING INFORMATION

- DYNAMESH DynaSilver™ is available in 328 linear foot (100 meter) rolls, slit to the following widths: 1" (25 mm), 2" (50 mm), or 3" (80 mm)

SHELF LIFE

- Store at 50 - 86°F (10 - 30°C) and 70% or lower relative humidity.
NOTE: Outside of this temperature range, adhesive strength and holding power may be reduced, making tape less able to adhere.
- Store away from moisture and chemicals.
- Store in airtight polyethylene or similar packaging.
- Avoid direct sunlight or close proximity to fluorescent lighting.
- Rolls of tape should be stacked and flat sheets should be stored flat.
- Avoid dropping or striking tape rolls.

NOTE: All technical information is published without warranty. The results displayed in this Technical Data Sheet are based on laboratory testing. The supplier declines any responsibility for incorrect use of these products which are manufactured and sold for industrial use only.

PROPERTIES

FINISH
Matte Silver

ADHESIVE STRENGTH (JIS Z 0237)
7.0 N / 25 mm*

BALL TACK (JIS Z 0237)
5±2*

HOLDING POWER (JIS Z 0237)
N.C/60 min*

MINIMUM APPLICATION
TEMPERATURE
50°F

* Values based on reference measurements and should not be considered guarantees of product performance.